



SolarEdge Single Phase Inverters



The best choice for SolarEdge enabled systems

- Superior efficiency (>97%)
- Small, lightweight and easy to install
- Built-in module-level monitoring receiver
- Communication to internet via broadband
- IP65 – Outdoor and indoor installation
- Excellent reliability with standard 12 year warranty



architects of energy™

Single Phase Inverters

SE3300/SE4000/SE5000/SE6000

All our inverters are part of SolarEdge's innovative system designed to provide superior performance at a competitive price.

The SolarEdge inverter combines a sophisticated, digital control technology and a one stage, ultra-efficient power conversion architecture to achieve superior performance – over 97% efficiency and best-in-class reliability. Our fixed-voltage technology ensures the inverter is always working at its optimal input voltage, regardless of the number of modules or environmental conditions.

A proprietary data monitoring receiver is integrated in the inverter and aggregates SolarEdge PowerBox performance data from each PV module. Multiple inverters can be connected in an RS485 bus or using a wireless Zigbee MESH network. The data from the inverters is transmitted to the web using an Ethernet connection or a wireless link and can be accessed via the SolarEdge Monitoring Portal for performance analysis, fault detection and troubleshooting.

This inverter can be fitted with a seamlessly attachable cabling duct for managing the installation wirings and it is light enough for a single person to install on a supplied bracket.

TECHNICAL DATA

	SE3300	SE4000	SE5000	SE6000	
OUTPUT					
Rated AC Power Output	3300	4000	5000	6000	W
Maximum AC Power Output	3300	4000	5000	6000	W
AC Output Voltage (Nominal)	230				Vac
AC Output Voltage Range	184 - 264.5				Vac
AC Frequency (Nominal)	50				Hz
AC Frequency Range	47.5 - 50.2				Hz
Maximum Continuous Output Current	18	22	27	30	A
Total Harmonic Distortion (THD) at Maximum Power	< 3				%
Power Factor	> 0.99				
Residual Current Detector / Residual Current Step Detector	300 / 30				mA
Maximum DC Injection	130				mA
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes				
INPUT					
Recommended Maximum DC Power (Module STC)	3500	4200	5300	6200	W
Transformer-less, Ungrounded	Yes				
Maximum Input Voltage	500				Vdc
Nominal DC Input Voltage	350				Vdc
Maximum Input Current	13	16	20	23	Adc
Reverse-Polarity Protection	Yes				
Ground-Fault Isolation Detection	600k Ω Sensitivity				
Maximum Inverter Efficiency	97.6				%
European Weighted Efficiency	97.2	97.3	97.2	97.1	%
Nighttime Power Consumption	< 2.5				W
STANDARD COMPLIANCE					
Safety	IEC-62103 (EN50178), Draft IEC-62109, UL1741				
Grid Connection Standards	VDE 0126-1-1, AS-4777, RD-1663, DK 5940, IEC61000-3-11, IEC61000-3-12, IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC part15 class B				
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC part15 class B				
WEEE, RoHS	Yes				
INSTALLATION SPECIFICATIONS					
AC Output	Cable Gland - diameter 13-18 mm				
DC Input	MC3 / MC4 / Tyco				
Dimensions (WxLxH)	540x315x191				mm
Weight	23				kg
Cooling	Natural Convection				
Operating Temperature Range	-20 - +50				$^{\circ}$ C
Protection Rating	IP65 - Outdoor and Indoor				
Bracket Mounted (Bracket Provided), Optional Attachable Cabling Duct (EU), Integral DC Switch (US)					

USA 2225 East Bayshore Rd., Suite 200, Palo Alto CA 94303, USA

Germany Königstr. 5, 01097 Dresden, Germany

Japan B-9 Ariake Frontier Building, 3-7-26 Ariake, Koto-Ku, Tokyo 135-0063, Japan

Israel 6 HaHarash St. P.O.Box 7349, Neve Neeman, Hod Hasharon 45240, Israel

www.solaredge.com

solaredge
architects of energy™